

Vm

- [Create a vm](#)
- [Resize vm disk](#)
- [Disable swap](#)
- [SSH setup](#)
- [Arch install](#)

Create a vm

Using proxmox webUI, don't forget to check Qemu agent.

After having installed it EACH vm, don't forget to remove CD/DVD iso as it won't be used anymore, otherwise you'll get an error if you need to migrate your vm.

Resize vm disk

- Resize disk in the vm's hardware tab using proxmox webUI
- Find disk's name (usually for us sda)
- launch parted `parted /dev/sda`
- use `print` to print the current partition table (replace sda with disk's name)
- resize your target partition with `resizepart <PART's ID> 100%`
- Finally, `quit` parted and run `resize2fs /dev/sda{PART's ID}`

Useful : <https://stackoverflow.com/questions/57302142/why-df-h-and-lsblk-show-different-sizes-of-my-one-and-only-xvda1>

Source :

DON'T DO PART 2 AND 3, do only one of them

Part 3 is a replacement or part 2.

https://pve.proxmox.com/wiki/Resize_disks

Disable swap

If you have GParted open, close it. Its Swapoff feature does not appear to be permanent.

Open terminal and become root (su); if you have sudo enabled, you may also do for example sudo -i; see man sudo for all options):

```
sudo -i (Or use sudo for each command)
```

Turn off the particular swap partition and / or all of the swaps:

```
swapoff --all
```

Make 100% sure the particular swap partition partition is off:

```
cat /proc/swaps
```

Open a text editor you are skilled in with this file, e.g. nano if unsure:

```
nano /etc/fstab
```

Comment out / remove the swap partition's UUID, e.g.:

```
# UUID=1d3c29bb-d730-4ad0-a659-45b25f60c37d none swap sw 0 0
```

Open a text editor you are skilled in with this file, e.g. nano if unsure:

```
nano /etc/initramfs-tools/conf.d/resume
```

Comment out / remove / change with 'none' the previously identified swap partition's UUID, e.g.:

```
RESUME=none
```

If your swap is encrypted, do the same with /etc/crypttab.

SSH setup

```
28 sudo vim /etc/ssh/sshd_config.d/disable_root_login.conf
29 /etc/init.d/ssh reload
30 sudo systemctl restart ssh
```

```
sudo vim /etc/ssh/sshd_config.d/disable_root_login.conf
sudo systemctl restart sshd
```

```
arthur_wambst@wingsBackup:~$ cat /etc/ssh/sshd_config.d/disable_root_login.conf
```

```
sudo echo "ChallengeResponseAuthentication no\nPasswordAuthentication no\nUsePAM\nno\nPermitRootLogin no" > /etc/ssh/sshd_config.d/disable_root_login.conf
```

```
export PORT=.
ssh-copy-id -p $PORT napo280.ovh
ssh napo280.ovh -p $PORT
```

```
cat <<EOF | sudo tee /etc/ssh/sshd_config.d/disable_root_login.conf
ChallengeResponseAuthentication no
PasswordAuthentication no
UsePAM no
PermitRootLogin no
EOF
sudo systemctl restart sshd
```

```
arthur_wambst@WORK-KARTOFFEL:~/TP_assembleur$ ssh-copy-id -p 2331 napo280.ovh
```

Arch install

```
fdisk /dev/sda
```

```
g  
n  
w
```

```
mkfs.ext4 /dev/sda1  
pacman -Sy  
pacman -S reflector  
cp /etc/pacman.d/mirrorlist /etc/pacman.d/mirrorlist.bak  
reflector -c "FR" -f 12 -l 10 -n 12 --save /etc/pacman.d/mirrorlist  
mount /dev/sda1 /mnt  
pacstrap /mnt base linux linux-firmware vim nano  
genfstab -U /mnt >> /mnt/etc/fstab  
arch-chroot /mnt  
pacman -Sy grub sudo cni-plugins dhcpd qemu-guest-agent openssh  
systemctl enable --now sshd  
systemctl enable --now dhcpd  
echo HOSTNAME > /etc/hostname  
cat <<EOF | tee /etc/hosts  
127.0.0.1 localhost  
::1 localhost  
127.0.1.1 HOSTNAME  
EOF  
passwd
```

```
grub-install /dev/sda  
grub-mkconfig -o /boot/grub/grub.cfg  
useradd -m arthur_wambst  
usermod -aG wheel,audio,video,storage arthur_wambst  
passwd arthur_wambst
```

```
visudo
```

Change %wheel.... all (uncomment to allow...)

umount /mnt

shutdown now